



## **EL-SIE Firmware Update - Instructions for firmware update v1.14**

Any EL-SIE device purchased before the 2nd December 2020 may need this firmware update in order to enable EasyLog Cloud compatibility. Any EL-SIE data logger purchased after this date should already have this firmware installed.

1. Plug your EL-SIE device into your PC or Mac. 'USB' will then show on its display.
2. Open Chrome browser and enter the following in the address bar: <http://easylog.local/>
3. Select the "Update Firmware" option from the "?" button dropdown (top right of screen).
4. Right click the compressed folder, containing the firmware update and these instructions, that you have downloaded and click 'Extract all'. This will allow you to generate a new "unzipped" folder. Once generated, open this folder and select the 'Firmware Update' file stored inside (the file should have a .tar file extension).
5. Click "Continue" when prompted.
6. The logger should begin the update process.
7. Once complete, the logger will reset. The logger's green LED will light for a few seconds while the new firmware is written to the logger. Once that completes the logger will beep and show the new firmware revision on the LCD and then go back to the "USB" display assuming that it is still connected to the PC via the USB cable.
8. The webpage should automatically reconnect when it sees the logger come back online.

### **If your logger does not automatically restart logging, you may need to reconfigure your device.**

1. Plug your EL-SIE device into your PC or Mac. 'USB' will then show on its display.
2. Open your internet browser and enter the following in the address bar: <http://easylog.local/>
3. When you reconfigure your device, the data readings stored on-board will be erased. To ensure you keep your data, click the download data button at the top of the screen and download your data in whichever format you wish.  
Alternatively, you can upload your data to your EasyLog Cloud account for storage. This may need to be enabled for your account before you can do this. Call our team on +44 (0)1425 651111 or email [sales@filesthrutheair.com](mailto:sales@filesthrutheair.com) for support with this.

### **Do not continue with reconfiguration until you have safely stored any data that you wish to keep, somewhere off-board the device (either as a downloaded file or in your EasyLog Cloud account).**

4. Click the 'Home' button at the top of the web page.
5. Click 'Quick Start' and follow the setup process. Your previous settings should be remembered and pre-populated, so this should be quick and easy. However, pay particular attention to the start method for logging as you may wish to change this for immediate start if you used an alternative start method last setup.
6. Reconfiguration complete. You can unplug your device and it should restart logging according to your configured start method.

If you need any support with this firmware update or any other EL-SIE technicalities, please contact our technical support team:

Call: +44 (0)1425 651111

Email: [support@filesthrutheair.com](mailto:support@filesthrutheair.com)